

SNBC

Extraordinary
Value!

BTP-M280

Series Impact Receipt Printers



Preferred for POS, Bar & Kitchen Printer Applications

The BTP-M280 produces either receipts or kitchen orders faster than other popular impact printers. Featuring trouble-free drop-and-print paper loading, it is adjustable to accommodate 76, 70, or 58mm paper rolls. Print is clear and precise, allowing you to print long-lasting receipts with coupons, rebates and specials. User defined graphic logos are easily downloaded with SNBC's free utility software.

- Serial, Parallel, Ethernet and Wireless WiFi Interface Options
- Two Color Print – Uses Industry Standard ERC-38 Ribbon Cartridge
- Stores and Prints Logo Images
- Extraordinary Reliability
- Contains Everything Necessary in the Carton – Including Communications Cables

BTP-M280A – Auto Cutter / Paper Take Up



BTP-M280D – Manual Tear



BTP-M280 Series Impact Receipt Printers



Drop and Print Paper Loading with Built-In Paper Width Selector



Built-In Wall Mount Capability and Optional Audio/Visual Print Messenger



Conceal the Power Supply in the Optional Power Supply Cover



Includes Everything Necessary in the Carton

Features

Proven impact printing technology preferred for POS kitchen printer applications.

- Everything You Need is in the Carton
- Serial, Parallel, Ethernet, USB and Wireless WiFi Interface Boards Available
- Uses the Same Interface Boards as Other SNBC Printers
- Auto-Cutter with Selectable Full or Partial Cut (BTP-M280A)
- Two-Color Print – Uses Industry Standard ERC-38 Ribbon Cartridge
- Fast 4.7 Lines per Second Print Speed
- Drop and Print Paper Loading
- Built-In Wall Mount Capability
- Paper-End Sensor
- Adjustable Paper Near-End Sensor
- No Dip Switches
- Includes Starter Paper Roll, Paper Width Selector, Appropriate Communications Cable, Power Adapter and Cord, Ribbon, CD-ROM with Drivers, Utilities and User's Manual

Optional Devices / Upgrades

Upgrade your printer with these easy-to-add options:

- Serial, Parallel, Ethernet and Wireless WiFi Interface Boards Are User Interchangeable
- Audio/Visual Print Messenger – For Noisy Kitchens – Alarm Sounds and Light Flashes When a New Order is Printed
- Power Supply Cover
- Powered USB Cable

Ports and Connectivity

A Choice of Serial (Shown), Parallel, USB, Ethernet or Wireless WiFi Interface Boards Available

B Cash Drawer

C DC 24V Power-In

Specifications

Max. Print Speed:	4.7 Lines per Second / 19.6mm per Second	
Printing Method:	Impact	
Characters Per Line –	Font A:	33 / 35
	Font B:	40 / 42
Characters Size –	Font A:	9 x 9
	Font B:	7 x 9
Paper Roll Type –	Width:	76 / 69.5 / 57.5mm ± 0.5mm
	Maximum Diameter:	83mm
	Paper Thickness:	0.06mm ~ 0.085mm
	Auto Paper Cutting Method:	Auto-Cutter with Selectable Full or Partial Cut
	BTP-M280D Cutting Method:	Manual Tear
Inking Supply:	ERC-38 Ribbon Cartridge (Black/Red)	
Reliability –	MTBF:	300,000 Hours
	MCBF:	18,000,000 Lines
	Printhead Life:	150,000,000 Characters
	Cutter Life:	1,500,000 Cuts
Character Set –	Alphanumeric:	95
	International:	13
	Graphic:	128 x 8 Page
Interpreter:	ESC/POST™	
Interface:	Serial / Parallel / Ethernet / USB / Wireless WiFi	
Driver –	32 bit & 64 bit:	POSReady 2009 / Windows 7 / Server 2003 / Server 2008 / VISTA / XP-PRO / 2000 Server / 2000 Professional
Drawer Port:	2 Port (+24VDC) with Drawer Compulsion	
Data Buffer – Receive Buffer RAM:	4 KB RAM	
	RAM Bitmap:	8 KB
	Flash Bitmap:	128 KB
Power Supply:	AC 100 ~ 240 V, 50/60 Hz Adapter Included	
Current/Power Usage:	1.5A / 36W	
Operating Temperature:	40° ~ 114°F (5° ~ 45°C)	
Operating Humidity:	20% ~ 90% RH (Non-Condensing)	
Dimensions /	M280A:	6-5/16"W x 6-5/8"H x 11-3/4"D / 10.10 lbs.
Ship Weight –	M280B:	6-5/16"W x 5-11/16"H x 9-5/8"D / 9.50 lbs.
	M280D:	6-5/16"W x 5-11/16"H x 9-5/8"D / 9.50 lbs.
Safety and EMI:	FCC / RoHS	

