

PORTI-AP60



General Features

Ultra small size rack mount printer.
 Very silent printing thru direct thermal printing method
 High speed (50mm/sec)
 High resolution (203dpi:8dots/mm)
 Serial (RS-232C or RS-485), Parallel interface
 Support text and graphic printing.
 Easier maintenance with self-diagnostics
 Auto cutting.

Applications

Receipt, Coupon, Ticket, Daily Report Kitchem Delivery, Bar-code, Industrial machine

Technical Specifications

Item	Specification	
Printing	Direct thermal line printing	
Characters per line	42cpl	
Character size	Eng. : 9x24dots, 12x24dots Kor. : 16x24dots [24x24dots]	
Resolution	203dpi, 8dots/mm	
Print width	2-inch (48mm, 384dots)	
Printing speed	50mm/sec	
Dimensions (WxDxH)	107.2x109.1x90.6 mm	
Weight	451g (including roll paper)	
Paper supplied	Thermal roll paper, label roll (57mm wide, 60Φ)	
Barcode supported	PDF417, QR code, Data matrix(2-dimension), Code128, Code39, I2/5, Code93, UPC, EAN(KAN, JAN), CODABAR	
Receive buffer size	1MB	
Input Power	9VDC, Standby 60mA and Max 3.0A [standard] 12~24VDC, Standby 60mA and Max 3.0A [Parallel]	
Operating temperature	-10°C~50°C	
Storage temperature	-10°C~70°C	
MCBF(Mean Cycle Between failure)	Mechanical	37,000,000 lines
	Head	Approximately 50 Km