

3, 4INCH PANEL PRINTER

PORTI-P340, P440



Porti-P340



Porti-P440

Features

- Ultra small size rack mount printer.
- Very silent printing thru direct thermal printing method
- High speed(50mm/sec)
- UART or TTL interface.
- Support text and graphic printing.
- Support bit-image (logo) download.
- Easier paper loading by CLAMSHELL design.
- Easier maintenance with self-diagnostics.



WOOSIM Panel printer series

Specification

| Model | P340 | P440 |
|---------------------|---|--------------------------------------|
| Printing method | Direct thermal line printing | |
| Characters per line | 64cpl (MAX) | 92cpl (MAX) |
| Characters size | Eng : 9x24 dots, 12x24 dots Kor : 16x24 dots [24x24 dots] | |
| Optional Characters | Simplified/Traditional Chinese, Arabic, Cyrillic, Russian, Turkish, Greek, Japanese, Persian, Latin9 and Others upon request. | |
| Resolution | 203 dpi, 8 dots/mm | |
| Print width | 3-inch (72mm, 576 dots) | 4-inch (104mm, 832 dots) |
| Printing speed | 50 mm/sec (MAX) | 50 mm/sec (MAX) |
| Dimensions | 110 x 77.7 x 49.1 mm | 143 x 77.7 x 49.1 mm |
| Weight | 177g | 227g |
| Interface | · UART(RS-232C or TTL) | |
| Paper supplied | Thermal roll paper (80mm wide, 40Ø) | Thermal roll paper (113mm wide, 40Ø) |
| | Paper thickness : 60±5µm | |
| Barcodes | 1-dimension:Code128, EAN 128, Code39, I2/5, Code93, UPC, EAN, KAN, JAN, CODABAR 2-dimension:PDF417, QR Code, DATA Matrix | |
| Driver | Microsoft Windows XP / VISTA / 7 , Windows CE, Linux, Android OS driver compatible | |
| Input power | 9VDC, Standby 60mA and MAX 3A | |

Applications

Test & Measurement, Transportation, Health care, ATM, Coupon, Self service, Kiosks, Electronic voting systems.

